

BLANK PAGE



IS 8271 (Part 6/Sec 5): 1991

भारतीय मानक

आवृति नियंत्रण और चयन में प्रयुक्त क्वार्टज् क्रिस्टल इकाइयाँ — विशिष्टि

भाग 6 दोलकों के लिये बी एफ श्रेणी अनुभाग 5 क्वार्टज किस्टल इकाई टाइप बी एफ-05

Indian Standard

QUARTZ CRYSTAL UNITS USED FOR FREQUENCY CONTROL AND SELECTION — SPECIFICATION

PART 6 SERIES BF FOR OSCILLATORS
Section 5 Quartz Crystal Unit Type BF-05

UDC 621:373:5

© BIS 1991

BUREAU OF INDIAN STANDARDS MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002 Piezoelectric Devices for Frequency Control and Selection Sectional Committee, LTD 12

FOREWORD

This Indian Standard (Part 6/Sec 5) was adopted by the Bureau of Indian Standards, after the draft finalized by the Piezoelectric Devices for Frequency Control and Selection Sectional Committee had been approved by the Electronics and Telecommunication Division Council.

This standard shall be read in conjunction with IS 8271 (Part 1): 1981 'Specification for quartz crystal units used for frequency control and selection: Part 1 General requirements and tests (first revision)'.

This standard is based on JSS 50911 (1971) 'Detail specification for crystal unit, quartz, styles QC 40 and QC 41' issued by the Directorate of Standardization, Ministry of Defence, India. The type of quartz crystal unit covered in this standard is equivalent to style QC 40 of JSS 50911 (1971).

For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test or analysis, shall be rounded off in accordance with IS 2:1960 'Rules for rounding off numerical values (revised)'. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

Indian Standard

QUARTZ CRYSTAL UNITS USED FOR FREQUENCY CONTROL AND SELECTION — SPECIFICATION

PART 6 SERIES BF FOR OSCILLATORS Section 5 Quartz Crystal Unit Type BF-05

1 SCOPE

1.1 This standard specifies detail requirements for the characteristics of quartz crystal unit. Type BF-05 used for frequency control and selection in oscillators:

2 REFERENCES

2.1 The following Indian Standards have been referred to in this standard:

| IS No. | Title | | |
|------------------------|---|--|--|
| 4570 | Specification for crystal unit | | |
| (Part 5): 1984 | holders: Part 5 Metal, solder seal, two-pin, crystal unit holders types BF, BF/1 and BG, | | |
| | BG/1 | | |
| 8271 (Part 1): 1981 | Specification for quartz crystal units used for frequency control and selection: Part 1 General requirements and test (first revision). | | |

3 OUTLINE AND DIMENSIONS

3.1 Holder outline shall conform to Type BF [see IS 4570 (Part 5): 1984].

4 MARKING

4.1 See 8 of IS 8271 (Part 1): 1981.

5 CONSTRUCTION AND WORKMANSHIP

5.1 See 7 of IS 8271 (Part 1): 1981.

6 TEST SCHEDULE AND DETAIL REQUIREMENTS

6.1 General Conditions for Test

See 9.2 of IS 8271 (Part 1): 1981.

6.2 Test Schedule

The sequence and grouping of type, routine and acceptance tests shall be in accordance with 9.1 of IS 8271 (Part 1): 1981.

6.3 Detail Requirements

The detail requirements applicable to this particular type of crystal unit shall be as specified in Table 1.

Table 1 Detail Requirements of Quartz Crystal Unit Type BF-05

(Clause 6.3)

| Sl No. | Characteristics | Requirements |
|---------------|---|--|
| -(1) | (2) | (3) |
| a) Type | of holder | BF (See 3) |
| b) Freq | uency range | 50 to 125 MHz |
| | uency tolerance: rating temperature range | ± 50 ppm |
| d) Load | l capacitance | Infinity |
| e) Mod | e of oscillation | Third mechanical overtone |
| f) Oper | ating temperature range | -55° C to $+105^{\circ}$ C |
| g) Test | set, calibration values and rated drive level | See Table 2 |
| h) Capa | acitance shunt | 7 pF, Max |
| i) 5 | nance resistance; 0 to 90 MHz 0 + to 125 MHz | 50 ohms, <i>Max</i> 60 ohms, <i>Max</i> |
| (Pa: i) F | ck [as per 9.15 (Severity A) of IS 8271 ct 1): 1981]: Prequency change permitted Resonance resistance change permitted | ± 5 ppm ± 10 percent |
| IS 8: i) F | ation [as per 9.16.1 (Severity A) of 271 (Part 1): 1981]: requency change permitted tesonance resistance change permitted | ± 5 ppm ± 10 percent |
| q) Agei | | ± 5 ppm |

IS 8271 (Part 6/Sec 5): 1991

Table 2 Test Set, Calibration Values and Rated Drive Level
[Table 1 (g)]

| Frequency Range | Calibration Values | | Rated Drive Level | Test Set |
|------------------|--------------------|--------------------------|------------------------|------------|
| | Resistance | Resister Voltage Drop | | |
| MHz | ohms | volt | $\mathbf{m}\mathbf{W}$ | |
| (1) | (2) | (3) | (4) | (5) |
| Up to 100 | 60 | 0.35 | 2.0 ± 0.4 | TS-683/TSM |
| Above 100 | 60 | 0.35 | 2.0 ± 0.4 | AN/TSM-15 |

Standard Mark

The use of the Standard Mark is governed by the provisions of the Bureau of Indian Standards Act, 1986 and the Rules and Regulations made thereunder. The Standard Mark on products covered by an Indian Standard conveys the assurance that they have been produced to comply with the requirements of that standard under a well defined system of inspection, testing and quality control which is devised and supervised by BIS and operated by the producer. Standard marked products are also continuously checked by BIS for conformity to that standard as a further safeguard. Details of conditions under which a licence for the use of the Standard Mark may be granted to manufacturers or producers may be obtained from the Bureau of Indian Standards.

Bureau of Indian Standards

BIS is a statutory institution established under the Bureau of Indian Standards Act, 1985 to promote harmonious development of the activities of standardization, marking and quality certification of goods and attending to connected matters in the country.

Copyright

BIS has the copyright of all its publications. No part of these publications may be reproduced in any form without the prior permission in writing of BIS. This does not preclude the free use, in the course of implementing the standard, of necessary details, such as symbols and sizes, type or grade designations. Enquiries relating to copyright be addressed to the Director (Publication), BIS.

Revision of Indian Standards

Indian Standards are reviewed periodically and revised, when necessary and amendments, if any, are issued from time to time. Users of Indian Standards should ascertain that they are in possession of the latest amendments or edition. Comments on this Indian Standard may be sent to BIS giving the following reference:

Doc: No. LTD 12 (1402)

A A NT -

Amendments Issued Since Publication

| Amend No. | Date of Issue | Text Affected |
|--|---|---|
| | | |
| | BUREAU OF INDIAN STANDARDS | • |
| Headquarters: | en per en | · · · · · · · · · · · · · · · · · · · |
| Manak Bhavan, 9 Ba Telephones: 331 01 | hadur Shah Zafar Marg, New Delhi 110002 31, 31 13 75 | Telegrams: Manaksanstha (Common to all Offices) |
| Regional Offices: | | Telephone |
| | avan, 9 Bahadur Shah Zafar Marg LHI 110002 | { 331 01 31 331 13 75 |
| Eastern: 1/14 C.I.T CALCUT | . Scheme VII M, V.I.P. Road, Maniktola ΓΑ 700054 | 37 86 62 |
| Northern: SCO 445 | -446, Sector 35-C, CHANDIGARH 160036 | 2 18 43 |
| Southern: C.I.T. Ca | impus, IV Cross Road, MADRAS 600113 | 41 29 16 |
| Western: Manakala BOMBAY | ya, E9 MIDC, Marol, Andheri (East) 7 400093 | 6 32 92 95 |
| Branches: AHMAD | OABAD. BANGALORE. BHOPAL. BHUBANES | HWAR. |

COIMBATORE. FARIDABAD. GHAZIABAD. GUWAHATI.

HYDERABAD, JAIPUR, KANPUR, PATNA, THIRUVANANTHAPURAM.